



PERFORMANCE DATA SHEET

A. O. Smith water filtration systems are obsessively engineered to provide you with clean water. A Performance Data Sheet is your proof that the system performs; the data sheet discloses test results of each filtration system against NSF water filtration testing criteria and standards.

NSF-International is an independent certification organization that develops test protocols and standards for drinking water filtration systems. NSF requires that each contaminant is reduced by a certain percentage specific to the water filtration system.

Take a look. Review the data. If you need help or have a question, we've got you covered.

Give us a call at
877.333.7108

For additional information, visit www.nsf.org.

Performance Data Sheet for the A. O. Smith CWM Clean Water Machine					
Models	Replacement	Operating pressure range	Rated capacity	Operating temp. range	Rated flow
AO-CWM	AO-US-100-R	20-70 psi 137-482 kPa	320 gallons 1200 liters	40-90° F 4.44-32.2° C	0.5 gpm 1.8 lpm
Manufactured by: A. O. Smith Corporation 11270 West Park Place Milwaukee, WI 53224 877.333.7108					



This system has been tested according to NSF/ANSI 42, 53, & 401 for reduction of the substances listed below. The concentration of the indicated substances in water entering the system was reduced to a concentration less than or equal to the permissible limit for water leaving the system, as specified in NSF/ANSI 42, 53, & 401.

NSF/ANSI 42	Minimum Reduction	Overall % Reduction	Results
Chlorine Reduction, Free Available	<0.5 mg/l	96.06%	Pass
Chloramine Reduction, Free Available	<0.5 mg/l	96.06%	Pass
Particulate Reduction	85%	99.9%	Pass

NSF/ANSI 53	Minimum Reduction	Overall % Reduction	Results
Cyst Live Cryptosporidium & Giardia	99.95%	>99.95%	Pass
Mercury Reduction pH 8.5	<2 ug/L	>96.7%	Pass
Mercury Reduction pH 6.5	<2 ug/L	>96.6%	Pass
Lead Reduction pH 6.5	<10 ug/L	>99.3%	Pass
Lead Reduction pH 8.5	<10 ug/L	>99.4%	Pass
MTBE Reduction	<5 ug/L	91.2%	Pass
Perfluorooctanoic acid (PFOA) & Perfluorooctane sulfonate (PFOS)	0.07 ug/L	95.8%	Pass
Turbidity	<0.5 NTU	99.1%	Pass
VOC Surrogate Test	See Table 8.2	95%	Pass
Asbestos	99%	>99%	Pass

NSF/ANSI 401	Maximum Concentration	Minimum Reduction	Overall % Reduction	Results
Atenolol	30 ng/L	94.2%	94.2%	Pass
Bisphenol A	300 ng/L	98.80%	98.9%	Pass
Carbamazepine	200 ng/L	98.6%	98.6%	Pass
DEET	200 ng/L	98.7%	98.7%	Pass
Estrone	20 ng/L	96.30%	96.5%	Pass
Ibuprofen	60 ng/L	95.3%	95.4%	Pass
Linuron	20 ng/L	96.6%	96.6%	Pass
Meprobamate	60 ng/L	94.7%	94.7%	Pass
Metolachlor	200 ng/L	98.6%	98.6%	Pass
Naproxen	20 ng/L	96.4%	96.4%	Pass
Nonyl phenol	200 ng/L	97.50%	97.5%	Pass
Phenytol	30 ng/L	95.50%	95.6%	Pass
TCEP	700 ng/L	98%	98%	Pass
TCPP	700 ng/L	97.8%	97.8%	Pass
Trimethoprim	20 ng/L	96.7%	96.7%	Pass

Table 8.2 – Performance data sheet reduction claims for organic chemicals included by surrogate testing

VOCs (by surrogate testing using chloroform)	Drinking water regulatory level (MCL/MAC) mg/L	Influent/Unfiltered	Effluent/Filtered	Percent Reduction
alachlor	0.002	0.050	0.001	>98%
atrazine	0.003	0.100	0.003	>97%
benzene	0.005	0.081	0.001	>99%
carbofuran	0.04	0.190	0.001	>99%
carbon tetrachloride	0.005	0.078	0.0018	98%
chlorobenzene	0.1	0.077	0.001	>99%
chloropicrin	—	0.015	0.0002	99%
2,4-D	0.07	0.110	0.0017	98%
dibromochloropropane (DBCP)	0.0002	0.052	0.00002	>99%
o-dichlorobenzene	0.6	0.080	0.001	>99%
p-dichlorobenzene	0.075	0.040	0.001	>98%
1,2-dichloroethane	0.005	0.088	0.0048	95%
1,1-dichloroethylene	0.007	0.083	0.001	>99%
cis-1,2-dichloroethylene	0.07	0.170	0.0005	>99%
trans-1,2-dichloroethylene	0.1	0.086	0.001	>99%
1,2-dichloropropane	0.005	0.080	0.001	>99%
cis-1,3-dichloropropylene	—	0.079	0.001	>99%
dinoseb	0.007	0.170	0.0002	99%
endrin	0.002	0.053	0.00059	99%
ethylbenzene	0.7	0.088	0.001	>99%
ethylene dibromide (EDB)	0.00005	0.044	0.00002	>99%
haloacetonitriles (HAN)	—	0.022	0.0005	98%
bromochloroacetone	—	0.024	0.0006	98%
dibromoacetone	—	0.0096	0.0002	98%
dichloroacetone	—	0.015	0.0003	98%
trichloroacetone	—	0.0072	0.0001	99%
1,1-dichloro-2-propanone	—	0.0082	0.0003	96%
1,1,1-trichloro-2-propanone	—	0.0082	0.0003	96%
heptachlor (H-34, Heptox)	0.0004	0.025	0.00001	>99%
heptachlor epoxide	0.0002	0.0107	0.0002	98%
hexachlorobutadiene	—	0.044	0.001	>98%
hexachlorocyclopentadiene	0.05	0.060	0.000002	>99%
lindane	0.0002	0.055	0.00001	>99%
methoxychlor	0.04	0.050	0.0001	>99%
pentachlorophenol	0.001	0.096	0.001	>99%
simazine	0.004	0.120	0.004	>97%
styrene	0.1	0.150	0.0005	>99%
1,1,2,2-tetrachloroethane	—	0.081	0.001	>99%
tetrachloroethylene	0.005	0.081	0.001	>99%
toluene	1	0.078	0.001	>99%
2,4,5-TP (silvex)	0.05	0.270	0.0016	99%
tribromoacetic acid	—	0.042	0.001	>98%
1,2,4-trichlorobenzene	0.07	0.160	0.0005	>99%
1,1,1-trichloroethane	0.2	0.084	0.0046	95%
1,1,2-trichloroethane	0.005	0.150	0.0005	>99%
trichloroethylene	0.005	0.180	0.0010	>99%
trihalomethanes (THMs)		Influent/Unfiltered	Effluent/Filtered	Percent Reduction
bromodichloromethane (THM)	0.080	0.300	0.015	95%
bromoform (THM)				
chloroform (THM)				
chlorodibromomethane (THM)				
xylenes (total)	10	0.070	0.001	>99%



System tested and certified by NSF to NSF/ANSI Standard 42, 53, and 401 for the reduction of the claims specified on the Performance Data Sheet and at www.NSF.org.

- All contaminants reduced by this filter are listed.
- Not all contaminants listed may be present in your water.
- Does not remove all contaminants that may be present in tap water.



Filter is only to be used with cold water.



Systems certified for cyst reduction may be used on disinfected waters that may contain filterable cysts.



Filter usage must comply with all state and local laws.



See owner's manual for general installation conditions and needs plus manufacturer's limited warranty.



Testing was performed under standard laboratory conditions, actual performance may vary.



For use with municipally treated water only. Do not use with water that is microbiologically unsafe or of unknown water quality without adequate disinfection before or after the system.

Hoja de datos de rendimiento de la máquina de agua limpia CWM de A. O. Smith					
Modelos	Repuesto	Rango de presión de funcionamiento	Capacidad nominal	Rango de temp. de funcionamiento	Flujo nominal
AO-CWM	AO-US-100-R	137 a 482 kPa 20 a 70 psi	1211 litros 320 galones	4,44 a 32,2 °C 40 a 90 °F	1,8 lpm 0,5 gpm
Manufactured by: A. O. Smith Corporation 11270 West Park Place Milwaukee, WI 53224					



Este sistema ha sido probado de acuerdo con NSF/ANSI 42, 53 y 401 para la reducción de las sustancias enumeradas a continuación. La concentración de las sustancias indicadas en el agua que ingresa al sistema se redujo a una concentración menor o igual al límite permisible para el agua que sale del sistema, como se especifica en NSF/ANSI 42, 53 y 401.

NSF/ANSI 42	Reducción mínima	Porcentaje total de reducción	Resultados
Chlorine Reduction, Free Available	<0.5 mg/l	96.06 %	Aprobado
Chloramine Reduction, Free Available	<0.5 mg/l	96.06 %	Aprobado
Particulate Reduction	85 %	99.9 %	Aprobado

NSF/ANSI 53	Reducción mínima	Porcentaje total de reducción	Resultados
Cyst Live Cryptosporidium & Giardia	99.95 %	>99.95 %	Aprobado
Mercury Reduction pH 8.5	<2 ug/L	>96.7 %	Aprobado
Mercury Reduction pH 6.5	<2 ug/L	>96.6 %	Aprobado
Lead Reduction pH 6.5	<10 ug/L	>99.3 %	Aprobado
Lead Reduction pH 8.5	<10 ug/L	>99.4 %	Aprobado
MTBE Reduction	<5 ug/L	91.2 %	Aprobado
Perfluorooctanoic acid (PFOA) & Perfluorooctane sulfonate (PFOS)	0.07 ug/L	95.8 %	Aprobado
Turbidity	<0.5 NTU	99.1 %	Aprobado
VOC Surrogate Test	Ver tabla 8.2	95 %	Aprobado
Asbestos	99 %	>99 %	Aprobado

NSF/ANSI 401	Concentración máxima	Reducción mínima	Porcentaje total de reducción	Resultados
Atenolol	30 ng/L	94.2 %	94.2 %	Aprobado
Bisphenol A	300 ng/L	98.80 %	98.9 %	Aprobado
Carbamazepine	200 ng/L	98.6 %	98.6 %	Aprobado
DEET	200 ng/L	98.7 %	98.7 %	Aprobado
Estrone	20 ng/L	96.30 %	96.5 %	Aprobado
Ibuprofen	60 ng/L	95.3 %	95.4 %	Aprobado
Linuron	20 ng/L	96.6 %	96.6 %	Aprobado
Meprobamate	60 ng/L	94.7 %	94.7 %	Aprobado
Metolachlor	200 ng/L	98.6 %	98.6 %	Aprobado
Naproxen	20 ng/L	96.3 %	96.4 %	Aprobado
Nonyl phenol	200 ng/L	97.50 %	97.5 %	Aprobado
Phenytoin	30 ng/L	95.50 %	95.6 %	Aprobado
TCEP	700 ng/L	98 %	98 %	Aprobado
TCPP	700 ng/L	97.8 %	97.8 %	Aprobado
Trimethoprim	20 ng/L	96.7 %	96.7 %	Aprobado

Tabla 8.2 – Afirmaciones de reducción de la hoja de datos de rendimiento para productos químicos orgánicos incluidos por pruebas sustitutas

COV (según la prueba de sustitutos con el uso de cloroformo)	Nivel normativo de agua potable (NMC/CMA) mg/L	Entrante/ Sin filtrar	Saliente/ Filtrada	Porcentaje de reducción
alachlor	0.002	0.050	0.001	>98 %
atrazine	0.003	0.100	0.003	>97 %
benzene	0.005	0.081	0.001	>99 %
carbofuran	0.04	0.190	0.001	>99 %
carbon tetrachloride	0.005	0.078	0.0018	98 %
chlorobenzene	0.1	0.077	0.001	>99 %
chloropicrin	—	0.015	0.0002	99 %
2,4-D	0.07	0.110	0.0017	98 %
dibromochloropropane (DBCP)	0.0002	0.052	0.00002	>99 %
o-dichlorobenzene	0.6	0.080	0.001	>99 %
p-dichlorobenzene	0.075	0.040	0.001	>98 %
1,2-dichloroethane	0.005	0.088	0.0048	95 %
1,1-dichloroethylene	0.007	0.083	0.001	>99 %
cis-1,2-dichloroethylene	0.07	0.170	0.0005	>99 %
trans-1,2-dichloroethylene	0.1	0.086	0.001	>99 %
1,2-dichloropropane	0.005	0.080	0.001	>99 %
cis-1,3-dichloropropylene	—	0.079	0.001	>99 %
dinoseb	0.007	0.170	0.0002	99 %
endrin	0.002	0.053	0.00059	99 %
ethylbenzene	0.7	0.088	0.001	>99 %
ethylene dibromide (EDB)	0.00005	0.044	0.00002	>99 %
haloacetonitriles (HAN)				
bromochloroacetonitrile	—	0.022	0.0005	98 %
dibromoacetonitrile	—	0.024	0.0006	98 %
dichloroacetonitrile	—	0.0096	0.0002	98 %
trichloroacetonitrile	—	0.015	0.0003	98 %
haloketones (HK)				
1,1-dichloro-2-propanone	—	0.0072	0.0001	99 %
1,1,1-trichloro-2-propanone	—	0.0082	0.0003	96 %
heptachlor (H-34, Heptox)	0.0004	0.025	0.00001	>99 %
heptachlor epoxide	0.0002	0.0107	0.0002	98 %
hexachlorobutadiene	—	0.044	0.001	>98 %
hexachlorocyclopentadiene	0.05	0.060	0.000002	>99 %
lindane	0.0002	0.055	0.00001	>99 %
methoxychlor	0.04	0.050	0.0001	>99 %
pentachlorophenol	0.001	0.096	0.001	>99 %
simazine	0.004	0.120	0.004	>97 %
styrene	0.1	0.150	0.0005	>99 %
1,1,2,2-tetrachloroethane	—	0.081	0.001	>99 %
tetrachloroethylene	0.005	0.081	0.001	>99 %
toluene	1	0.078	0.001	>99 %
2,4,5-TP (silvex)	0.05	0.270	0.0016	99 %
tribromoacetic acid	—	0.042	0.001	>98 %
1,2,4-trichlorobenzene	0.07	0.160	0.0005	>99 %
1,1,1-trichloroethane	0.2	0.084	0.0046	95 %
1,1,2-trichloroethane	0.005	0.150	0.0005	>99 %
trichloroethylene	0.005	0.180	0.0010	>99 %
trihalomethanes (THMs)		Entrante/ Sin filtrar	Saliente/ Filtrada	Porcentaje de reducción
bromodichloromethane (THM)				
bromoform (THM)	0.080	0.300	0.015	95 %
chloroform (THM)				
chlorodibromomethane (THM)				
xylenes (total)	10	0.070	0.001	>99 %



Sistema probado y certificado por NSF según las normas 42, 53 y 401 de NSF/ANSI para la reducción de las afirmaciones especificadas en la hoja de datos de rendimiento y en www.NSF.org.

- Se indican todos los contaminantes que reduce este filtro.
- Es posible que no todos los contaminantes indicados estén presentes en su agua.
- No elimina todos los contaminantes que pueden estar presentes en el agua de la llave.



El filtro solo se debe usar con agua fría.



Es posible usar sistemas certificados para la reducción de quistes en aguas desinfectadas que puedan tener quistes filtrables.



El uso del filtro debe cumplir con todas las leyes estatales y locales.



Consulte el manual del propietario para conocer las condiciones y necesidades generales de instalación más la garantía limitada del fabricante.



Las pruebas se realizaron en condiciones de laboratorio estándar, el rendimiento real puede variar.



Solo para uso con agua tratada localmente. No usar con agua que no sea microbiológicamente segura o cuya calidad sea desconocida sin la desinfección previa o posterior adecuada del sistema.