Performanc	Performance Data Sheet for the A. O. Smith Advanced Direct Connect Filter					
Model	Replacement	Rated capacity	Operating temp. range	Rated flow	Operating Pressure Range	
AO-MF-ADV	AO-MF-ADV-R	784 gallons 2,967 liters	35-100° F 1.66°-37.78° C	1.5 gpm 5.67 lpm	10-125 psi 68.9-861 kPa	
Manu	ADV AO-MF-ADV-R 784 gallons 2,967 liters 1.66°-37.78° C 1.5 gpm 5.67 lpm 68.9-861 kPa  Manufactured by: A. O. Smith Corporation   11270 W Park PI #170, Milwaukee, WI 53224   877.333.7108					

Min Reduction Overall % Reduction Results



This system has been tested according to NSF/ANSI Standards 42, 53, & 401 for the reduction of the substances listed below. The concentration of the indicated substances in water entering the system was reduced to a concentration less than or equal to the permissible limit for water leaving the system, as specified in NSF/ANSI 42, 53, & 401.

0.5 //		
<0.5 mg/l	96.06%	Pass
<0.5 mg/l	96.06%	Pass
97.3%	99.4%	Pass
Min Reduction	Overall % Reduction	Results
99%	>99%	Pass
99.95%	>99.95%	Pass
<10 ug/L	>99.4%	Pass
<10 ug/L	>99.3%	Pass
<2 ug/L	>96.6%	Pass
<2 ug/L	>96.7%	Pass
<5 ug/L	86.6%	Pass
0.07 ug/L	95.8%	Pass
<0.5 NTU	99.1%	Pass
See Table 8.2	99.4%	Pass
	<0.5 mg/l 97.3%  Min Reduction 99% 99.95% <10 ug/L <10 ug/L <2 ug/L <2 ug/L <5 ug/L <0.5 NTU	<0.5 mg/l

NSF/ANSI 401	Maximum Concentration	Minimum Reduction	Overall % Reduction	Results
Atenolol	30 ng/L	94.2%	94.2%	Pass
Bisphenol A	300 ng/L	98.80%	98.9%	Pass
Carbamazepine	200 ng/L	98.6%	98.6%	Pass
DEET	200 ng/L	98.7%	98.7%	Pass
Estrone	20 ng/L	96.30%	96.5%	Pass
Ibuprofen	60 ng/L	95.3%	95.4%	Pass
Linuron	20 ng/L	96.6%	96.6%	Pass
Meprobamate	60 ng/L	94.7%	94.7%	Pass
Metolachlor	200 ng/L	98.6%	98.6%	Pass
Naproxen	20 ng/L	96.3%	96.4%	Pass
Nonyl phenol	200 ng/L	97.50%	97.5%	Pass
Phenytoin	30 ng/L	95.50%	95.6%	Pass
TCEP	700 ng/L	98%	98%	Pass
TCPP	700 ng/L	97.8%	97.8%	Pass
Trimethoprim	20 ng/L	96.7%	96.7%	Pass
Microplastics (particles 0.5 to <1 µm)	At least 10,000 particles/mL	97.3%	99.4%	Pass



NSF/ANSI 42



System certified by IAPMO R&T against NSF/ANSI Standards 42, 53, and 401 for the reduction of the claims specified on the Performance Data Sheet and at www.IAPMO.com.

- All contaminants reduced by this filter are listed.
- Not all contaminants listed may be present in your water.
- Does not remove all contaminants that may be present in tap water.
- The contaminants covered in NSF/ANSI 401 have been deemed as incidental/emerging compounds and have been detected in drinking water supplies at trace levels. These compounds can affect some consumers' perception of drinking water quality.
- . Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system.

Click here to view the system's warranty.



Filter is only to be used with cold water.



Systems certified for cyst reduction may be used on disinfected waters that may contain filterable cysts.



Testing was performed under standard laboratory conditions, actual performance may vary.

included by surrogate testir VOCs (by surrogate testing	Drinking water	Influent/ Unfiltered	Effluent/ Filtered	Percent Reduction
using chloroform)	regulatory level (MCL/ MAC) mg/L			
alachlor	0.002	0.050	0.001	>98%
atrazine	0.003	0.100	0.003	>97%
benzene	0.005	0.081	0.001	>99%
carbofuran	0.04	0.190	0.001	>99%
carbon tetrachloride	0.005	0.078	0.0018	98%
chlorobenzene	0.1	0.077	0.001	>99%
chloropicrin	_	0.015	0.0002	99%
2,4-D	0.07	0.110	0.0017	98%
dibromochloropropane (DBCP)	0.0002	0.052	0.00002	>99%
o-dichlorobenzene	0.6	0.080	0.001	>99%
p-dichlorobenzene	0.075	0.040	0.001	>98%
1,2-dichloroethane	0.005	0.088	0.0048	95%
1,1-dichloroethylene	0.007	0.083	0.001	>99%
cis-1,2-dichloroethylene	0.07	0.170	0.0005	>99%
trans-1,2-dichloroethylene 1,2-dichloropropane	0.1	0.086	0.001	>99%
cis-1,3-dichloropropylene	0.005	0.080	0.001	>99%
dinoseb	0.007	0.170	0.0002	99%
endrin	0.007	0.170	0.0002	99%
ethylbenzene	0.7	0.033	0.00033	>99%
ethylene dibromide (EDB)	0.00005	0.044	0.00002	>99%
haloacetonitriles (HAN)	0.00003	0.044	0.00002	>9970
bromochloroacetontrile	I_	0.022	0.0005	98%
dibromoacetontrile	_	0.024	0.0006	98%
dichloroacetontrile	_	0.0096	0.0002	98%
trichloroacetontrile	_	0.015	0.0003	98%
haloketones (HK)		0.015	0.0005	3070
1,1-dichloro-2-propanone	I_	0.0072	0.0001	99%
1,1,1-trichloro-2-propanone	I_	0.0082	0.0003	96%
heptachlor (H-34, Heptox)	0.0004	0.025	0.00001	>99%
heptachlor epoxide	0.0002	0.0107	0.0002	98%
hexachlorobutadiene	<u> </u>	0.044	0.001	>98%
hexachlorocyclopentadiene	0.05	0.060	0.000002	>99%
lindane	0.0002	0.055	0.00001	>99%
methoxychlor	0.04	0.050	0.0001	>99%
pentachlorophenol	0.001	0.096	0.001	>99%
simazine	0.004	0.120	0.004	>97%
styrene	0.1	0.150	0.0005	>99%
1,1,2,2-tetrachloroethane	_	0.081	0.001	>99%
tetrachloroethylene	0.005	0.081	0.001	>99%
toluene	1	0.078	0.001	>99%
2,4,5-TP (silvex)	0.05	0.270	0.0016	99%
tribromoacetic acid	_	0.042	0.001	>98%
1,2,4-trichlorobenzene	0.07	0.160	0.0005	>99%
1,1,1-trichloroethane	0.2	0.084	0.0046	95%
1,1,2-trichloroethane	0.005	0.150	0.0005	>99%
trichloroethylene	0.005	0.180	0.0010	>99%
trihalomethanes (THMs)		Influent/ Unfiltered	Effluent/ Filtered	Percent Reduction
bromodichloromethane (THM)				
bromoform (THM)	0.080	0.300	0.015	95%
chloroform (THM)	1		1	
chlorodibromomethane (THM)				