

Performance Data Sheet for the A. O. Smith 2-Stage Water Filter					
Models	Replacement	Operating pressure range	Rated capacity	Operating temp. range	Rated flow
AO-US-200	AO-US-200-R	20-80 psi 137-482 kPa	500 gallons 1892 Liters	40-90° F 4.44-32.2° C	0.5 gpm 1.9 lpm
Manufactured by: A. O. Smith Corporation 11270 W Park Pl #170, Milwaukee, WI 53224 877.333.7108					



This system has been tested according to NSF/ANSI Standards 42, 53, and 401 for reduction of the substances listed below. The concentration of the indicated substances in water entering the system was reduced to a concentration less than or equal to the permissible limit for water leaving the system, as specified in NSF/ANSI Standards 42, 53, and 401.

NSF/ANSI 42	Minimum Reduction	Overall % Reduction	Results
Chlorine, Free Available	≥50%	97.3%	Pass
Chloramine, Free Available	0.5 mg/l	91%	Pass
Particulate Reduction Class I (particles 0.5 to <1 µm)	≥85%	99.6%	Pass

NSF/ANSI 53	Minimum Reduction	Overall % Reduction	Results
Asbestos	99%	>99%	Pass
Cyst (microspheres)	99.95%	99.95%	Pass
Lead pH 6.5	5 ug/L	>99.7%	Pass
Lead pH 8.5	5 ug/L	99.6%	Pass
Mercury pH 6.5	0.002 mg/L (2 ug/L)	>96.2%	Pass
Mercury pH 8.5	0.002 mg/L (2 ug/L)	95.4%	Pass
MTBE	0.005 mg/L (5 ug/L)	85.5%	Pass
PFOA/PFOS	0.00002 mg/L	99.7%	Pass
Turbidity	0.5 NTU	99.34%	Pass
VOC Surrogate Test (as chloroform)	See Table 8.2	99.3%	Pass

NSF/ANSI 401	Maximum Concentration	Minimum Reduction	Overall % Reduction	Results
Atenolol	30 ng/L	94.7%	>94.7%	Pass
Bisphenol A	300 ng/L	93.2%	93.9%	Pass
Carbamazepine	200 ng/L	98.4%	>98.4%	Pass
DEET	200 ng/L	98.4%	>98.4%	Pass
Estrone	20 ng/L	94.8%	95.5%	Pass
Ibuprofen	60 ng/L	93.5%	94.6%	Pass
Linuron	20 ng/L	96.3%	>96.3%	Pass
Meprobamate	60 ng/L	94.6%	>94.6%	Pass
Metolachlor	200 ng/L	98.4%	>98.4%	Pass
Microplastics (particles 0.5 to <1 µm)	At least 10,000 particles/mL	≥85%	99.6%	Pass
Naproxen	20 ng/L	94.5%	95.5%	Pass
Nonyl phenol	200 ng/L	89.3%	92.3%	Pass
Phenytol	30 ng/L	95.4%	>95.7%	Pass
TCEP	700 ng/L	98%	>98%	Pass
TCPP	700 ng/L	97.9%	>97.9%	Pass
Trimethoprim	20 ng/L	96.1%	>96.1%	Pass

Table 8.2 – Performance data sheet reduction claims for organic chemicals included by surrogate testing

VOCs (by surrogate testing using chloroform)	Drinking water regulatory level (MCL/ MAC) mg/L	Influent/ Unfiltered mg/L	Effluent/ Filtered mg/L	Percent Reduction
alachlor	0.002	0.050	0.001	>98%
atrazine	0.003	0.100	0.003	>97%
benzene	0.005	0.081	0.001	>99%
carbofuran	0.04	0.190	0.001	>99%
carbon tetrachloride	0.005	0.078	0.0018	98%
chlorobenzene	0.1	0.077	0.001	>99%
chloropicrin	—	0.015	0.0002	99%
2,4-D	0.07	0.110	0.0017	98%
dimomochloropropane (DBCP)	0.0002	0.052	0.0002	>99%
o-dichlorobenzene	0.6	0.080	0.001	>99%
p-dichlorobenzene	0.075	0.040	0.001	>98%
1,2-dichloroethane	0.005	0.088	0.0048	95%
1,1-dichloroethylene	0.007	0.083	0.001	>99%
cis-1,2-dichloroethylene	0.07	0.170	0.0005	>99%
trans-1,2-dichloroethylene	0.1	0.086	0.001	>99%
1,2-dichloropropane	0.005	0.080	0.001	>99%
cis-1,3-dichloropropylene	—	0.079	0.001	>99%
dinoseb	0.007	0.170	0.0002	99%
endrin	0.002	0.053	0.00059	99%
ethylbenzene	0.7	0.088	0.001	>99%
ethylene dibromide (EDB)	0.00005	0.044	0.00002	>99%
haloacetonitriles (HAN)	—	—	—	—
bromochloroacetonitrile	—	0.022	0.0005	98%
dibromoacetonitrile	—	0.024	0.0006	98%
dichloroacetonitrile	—	0.0096	0.0002	98%
trichloroacetonitrile	—	0.015	0.0003	98%
haloketones (HK)	—	—	—	—
1,1-dichloro-2-propanone	—	0.0072	0.0001	99%
1,1,1-trichloro-2-propanone	—	0.0082	0.0003	96%
heptachlor (H-34, Heptox)	0.0004	0.025	0.00001	>99%
heptachlor epoxide	0.0002	0.0107	0.0002	98%
hexachlorobutadiene	—	0.044	0.001	>98%
hexachlorocyclopentadiene	0.05	0.060	0.000002	>99%
lindane	0.0002	0.055	0.00001	>99%
methoxychlor	0.04	0.050	0.0001	>99%
pentachlorophenol	0.001	0.096	0.001	>99%
simazine	0.004	0.120	0.004	>97%
styrene	0.1	0.150	0.0005	>99%
1,1,2,2-tetrachloroethane	—	0.081	0.001	>99%
tetrachloroethylene	0.005	0.081	0.001	>99%
toluene	1	0.078	0.001	>99%
2,4,5-TP (silvex)	0.05	0.270	0.0016	99%
tribromoacetic acid	—	0.042	0.001	>98%
1,2,4-trichlorobenzene	0.07	0.160	0.0005	>99%
1,1,1-trichloroethane	0.2	0.084	0.0046	95%
1,1,2-trichloroethane	0.005	0.150	0.0005	>99%
trichloroethylene	0.005	0.180	0.0010	>99%
trihalomethanes (THMs)	—	—	—	—
bromodichloromethane (THM)	0.080	0.300	0.015	95%
bromoform (THM)				
chloroform (THM)				
chlorodibromomethane (THM)	10	0.070	0.001	>99%
xylems (total)				



System tested and certified by WQA to NSF/ANSI Standards 42, 53, and 401 for the reduction of the claims specified on the Performance Data Sheet and at www.WQA.org.

- All contaminants reduced by this filter are listed.
- Not all contaminants listed may be present in your water.
- Does not remove all contaminants that may be present in tap water.
- The contaminants covered in NSF/ANSI 401 have been deemed as incidental/emerging compounds and have been detected in drinking water supplies at trace levels. These compounds can affect some consumers' perception of drinking water quality.



Filter is only to be used with cold water.



Systems certified for cyst reduction may be used on disinfected waters that may contain filterable cysts.



Testing was performed under standard laboratory conditions, actual performance may vary.